


**Norma
NUI**



L = 600-625-650-700 mm I = 500 mm

Ø10-Ø22; Ø24, Ø25, Ø26 = Tipo RS - RS type (Lucide -Bright)



11121

Codice - Code

| | |
|-------------------------------|----------------------|
| Materiale - Material | HSS |
| Tipo - Type | RS/RN |
| Angolo di punta - Point angle | 130°/118° |
| Affilatura - Point shape | A |
| Rivestimento - Coating | Vap-Ox/Lucide-Bright |

| d h8 mm | L mm | I mm | CM | in stock |
|---------|------|------|----|----------|
| 10 | 600 | 500 | 1 | o RS |
| 10,5 | 600 | 500 | 1 | o RS |
| 11 | 600 | 500 | 1 | o RS |
| 11,5 | 600 | 500 | 1 | o RS |
| 12 | 600 | 500 | 2 | o RS |
| 12,5 | 600 | 500 | 2 | o RS |
| 13 | 600 | 500 | 2 | o RS |
| 13,5 | 600 | 500 | 2 | o RS |
| 14 | 600 | 500 | 2 | o RS |
| 14,5 | 600 | 500 | 2 | o RS |
| 15 | 600 | 500 | 2 | o RS |
| 15,5 | 600 | 500 | 2 | o RS |
| 16 | 600 | 500 | 2 | o RS |
| 16,5 | 600 | 500 | 2 | o RS |
| 17 | 600 | 500 | 2 | o RS |
| 17,5 | 600 | 500 | 2 | o RS |
| 18 | 600 | 500 | 2 | o RS |
| 19 | 600 | 500 | 2 | o RS |
| 19,5 | 600 | 500 | 2 | o RS |
| 20 | 600 | 500 | 2 | o RS |
| 21 | 600 | 500 | 2 | o RS |
| 22 | 600 | 500 | 2 | o RS |
| 23 | 625 | 500 | 3 | o |
| 24 | 625 | 500 | 3 | o RS |
| 24,5 | 625 | 500 | 3 | o |
| 25 | 625 | 500 | 3 | o RS |
| 26 | 625 | 500 | 3 | o RS |
| 27 | 625 | 500 | 3 | o |
| 28 | 625 | 500 | 3 | o |
| 29,5 | 625 | 500 | 3 | o |
| 30 | 625 | 500 | 3 | o |
| 31 | 650 | 500 | 3 | o |
| 32 | 650 | 500 | 4 | o |

