



DIN
8375-77-
79



11510

11520

11530

Codice - Code

| | | | |
|-------------------------------|---------|--------|--------|
| Materiale - Material | HSS | HSS | HSS |
| Tipo - Type | RN 180° | RN 90° | RN 90° |
| Angolo di punta - Point angle | 118° | 118° | 118° |
| Affilatura - Point shape | | | |
| Rivestimento - Coating | | | |

| Vite Screw | D h8 mm | d h8 mm | I1 mm | L mm | I2 mm | CM | in stock | in stock | in stock |
|-------------------------|------------|------------|----------|---------|----------|----|----------|----------|----------|
| 11510 - DIN 8377 | | | | | | | | | |
| M5 | 10 | 5,5 | 87 | 168 | 13 | 1 | o | | |
| M6 | 11 | 6,6 | 94 | 175 | 15 | 1 | o | | |
| M8 | 15 | 9 | 114 | 212 | 19 | 2 | o | | |
| M10 | 18 | 11 | 130 | 228 | 23 | 2 | o | | |
| M12 | 20 | 13,5 | 140 | 238 | 27 | 2 | o | | |
| M14 | 24 | 15,5 | 160 | 281 | 31 | 3 | o | | |
| M16 | 26 | 17,5 | 165 | 286 | 35 | 3 | o | | |
| M18 | 30 | 20 | 175 | 296 | 39 | 3 | o | | |
| M20 | 33 | 22 | 185 | 334 | 43 | 4 | o | | |
| 11520 - DIN 8375 | | | | | | | | | |
| M5 | 11 | 5,5 | 94 | 175 | 13 | 1 | | o | |
| M6 | 13 | 6,6 | 101 | 182 | 15 | 1 | | o | |
| M8 | 17,2 | 9 | 130 | 228 | 19 | 2 | | o | |
| M10 | 21,5 | 11 | 150 | 248 | 23 | 2 | | o | |
| 11530 - DIN 8379 | | | | | | | | | |
| M8 | 9 | 6,8 | 81 | 162 | 21 | 1 | | | o |
| M10 | 11 | 8,5 | 94 | 175 | 25,5 | 1 | | | o |
| M12 | 13,5 | 10,2 | 108 | 189 | 30 | 1 | | | o |
| M14 | 15,5 | 12 | 120 | 218 | 34,5 | 2 | | | o |
| M16 | 17,5 | 14 | 130 | 228 | 38,5 | 2 | | | o |
| M18 | 20 | 15,5 | 140 | 238 | 43,5 | 2 | | | o |
| M20 | 22 | 17,5 | 150 | 248 | 47,5 | 2 | | | o |