



**13310**

**Codice - Code**

Materiale - Material	HSSE
Imbocco - Chamfer	CR15
Tolleranza - Tolerance	6H
Rivestimento - Coating	

MF d mm	p mm	L mm	l mm	d3 h9 mm	S h12 mm		in stock
4	0,5	63	7	2,8	2,1	3,5	●
5	0,5	70	8	3,5	2,7	4,5	●
6	0,75	80	10	4,5	3,4	5,2	●
8	0,75	80	10	6	4,9	7,2	●
8	1	90	13	6	4,9	7	●
9	1	90	13	7	5,5	8	●
10	0,75	90	12	7	5,5	9,2	●
10	1	90	12	7	5,5	9	●
10	1,25	100	12	7	5,5	8,8	●
12	1	100	14	9	7	11	●
12	1,25	100	14	9	7	10,75	●
12	1,5	100	14	9	7	10,5	●
14	1	100	16	11	9	13	●
14	1,25	100	16	11	9	12,75	●
14	1,5	100	16	11	9	12,5	●
15	1	100	16	12	9	14	●
15	1,5	100	16	12	9	13,5	●
16	1	100	16	12	9	15	●
16	1,5	100	16	12	9	14,5	●
18	1	110	20	14	11	17	●
18	1,5	110	20	14	11	16,5	●
20	1	125	20	16	12	19	●
20	1,5	125	20	16	12	18,5	●
20	2	140	20	16	12	18	●
22	1	125	20	18	14,5	21	●
22	1,5	125	20	18	14,5	20,5	●
24	1	140	22	18	14,5	23	●
24	1,5	140	22	18	14,5	22,5	●
24	2	140	22	18	14,5	22	●
25	1,5	140	22	18	14,5	23,5	●
25	2	140	22	18	14,5	23	●
27	1,5	140	22	20	16	25,5	●
27	2	140	22	20	16	25	●

