

**M**




DIN 371  
≤ M10

DIN 376  
≥ M12

2,5xD

PM HSS



VA inox - stainless steel

SYN per maschiatura rigida - synchronized

IK lubrificazione interna - internal cooling

SYN

IK



VA

13752



VA

13743



VA

13744

**Codice - Code**

Materiale - Material	PM HSS	PM HSS	PM HSS
Imbocco - Chamfer	C R45	C R50	C R50
Tolleranza - Tolerance	6H	6HX	6HX
Rivestimento - Coating	TiN	TiCN	TiCN

M d mm	p mm	L mm	I mm	d3 h9 mm	S h12 mm		in stock	in stock	in stock
3	0,5	56	5	3,5	2,7	2,5		o	
4	0,7	63	7	4,5	3,4	3,3		o	
5	0,8	70	8	6	4,9	4,2	o	o	o
6	1	80	10	6	4,9	5	o	o	o
8	1,25	90	13	8	6,2	6,8	o	o	o
10	1,5	100	15	10	8	8,5	o	o	o
12	1,75	110	18	9	7	10,2	o	o	o
14	2	110	20	11	9	12		o	o
16	2	110	20	12	9	14	o	o	o
18	2,5	125	25	14	11	15,5		o	o
20	2,5	140	25	16	12	17,5		o	o