


M

DIN 371
≤ M10

DIN 376
≥ M12

2xD



W materiali teneri - light materials

HR alta resistenza - heat resistant

TI per titanio e leghe - for titanium and alloys

IK lubrificazione interna - internal cooling

PM HSS



W
13781



HR
13731

IK



HR
13732



TI
13761

Codice - Code

Materiale - Material	HSSE	PMHSS	PM HSS	PM HSS
Imbocco - Chamfer	C R15	C R15	C R15	C R10
Tolleranza - Tolerance	6H	6HX	6HX	6HX
Rivestimento - Coating		Vap-Ox	TiCN	TiCN

M d mm	p mm	L mm	I mm	d3 h9 mm	S h12 mm		in stock	in stock	in stock	in stock
2	0,4	45	8	2,8	2,1	1,6	o			
2,5	0,45	50	9	2,8	2,1	2	o			
3	0,5	56	5	3,5	2,7	2,5	o	o		o
3,5	0,6	56	6	4	3	2,9	o	o		o
4	0,7	63	7	4,5	3,4	3,3	o	o		o
5	0,8	70	8	6	4,9	4,2	o	o	o	o
6	1	80	10	6	4,9	5	o	o	o	o
8	1,25	90	13	8	6,2	6,8	o	o	o	o
10	1,5	100	15	10	8	8,5	o	o	o	o
12	1,75	110	18	9	7	10,2	o	o	o	o
14	2	110	20	11	9	12	o	o	o	o
16	2	110	20	12	9	14	o	o	o	o
18	2,5	125	25	14	11	15,5	o	o	o	o
20	2,5	140	25	16	12	17,5	o	o	o	o