



$\leq 15xD$  Norma NUI



Nuova geometria, doppio bordino  
 New geometry, double margin

HM

m7 h6

IK lubrificazione interna - internal cooling

IK



15381

Codice - Code

Materiale - Material

Tipo - Type

Angolo di punta - Point angle

Affilatura - Point shape

Rivestimento - Coating

HM

RW

140°

C

TiAlN

d1 m7 mm	d2 h6 mm	L mm	l mm	in stock
1	3	60	20	o
1,1	3	60	22	o
1,2	3	60	24	o
1,3	3	60	25	o
1,4	3	60	27	o
1,5	3	60	27	o
1,6	3	65	32	o
1,7	3	65	32	o
1,8	3	65	35	o
1,9	3	65	35	o
2	3	65	35	o
2,1	3	75	40	o
2,2	3	75	40	o
2,3	3	75	40	o
2,4	3	75	45	o
2,5	3	75	45	o
2,6	3	80	48	o
2,7	3	80	48	o
2,8	3	80	50	o
2,9	3	80	50	o
3	3	100	60	o
3,1	3	100	60	o
3,2	6	100	60	o
3,3	6	100	60	o
3,4	6	100	60	o
3,5	6	100	60	o
3,6	6	108	68	o
3,7	6	108	68	o
3,8	6	108	68	o
3,9	6	108	68	o
4	6	108	68	o
4,1	6	115	78	o
4,2	6	115	78	o
4,3	6	115	78	o

